

EFDA-JET-CP(07)03/57

M.F.F. Nave, L.–G. Eriksson, T. Hellsten, K-D. Zastrow, B. Alper, Y. Andrew, R. Barnsley, J. Brzozowski, K. Crombé, A. Czarnecka, M. von Hellermann, J.Ongena and JET EFDA contributors

# Toroidal Rotation in Ohmic and RF Heated JET Plasmas

"This document is intended for publication in the open literature. It is made available on the understanding that it may not be further circulated and extracts or references may not be published prior to publication of the original when applicable, or without the consent of the Publications Officer, EFDA, Culham Science Centre, Abingdon, Oxon, OX14 3DB, UK."

"Enquiries about Copyright and reproduction should be addressed to the Publications Officer, EFDA, Culham Science Centre, Abingdon, Oxon, OX14 3DB, UK."

## Toroidal Rotation in Ohmic and RF Heated JET Plasmas

M.F.F. Nave<sup>1</sup>, L.–G. Eriksson<sup>2</sup>, T. Hellsten<sup>3</sup>, K-D.Zastrow<sup>4</sup>, B.Alper<sup>4</sup>, Y. Andrew<sup>4</sup>, R. Barnsley<sup>4</sup>, J.Brzozowski<sup>3</sup>, K.Crombé<sup>5</sup>, A.Czarnecka<sup>6</sup>, M. von Hellermann<sup>7</sup>, J.Ongena<sup>8</sup> and JET EFDA contributors\*

 <sup>1</sup>Associação EURATOM/IST, Centro de Fusão Nuclear, 1049-001 Lisbon, Portugal
<sup>2</sup>Association EURATOM-CEA, CEA/DSM/DRFC, CEA-Cadarache, F-13108 St. Paul lez Durance, France <sup>3</sup>Euratom-VR Association, Stockholm, Sweden
<sup>4</sup>EURATOM-UKAEA Fusion Association, Culham Science Centre, OX14 3DB, Abingdon, OXON, UK
<sup>5</sup>Association EURATOM-Belgian State, Department of Applied Physics Ghent University, B-9000 Ghent, Belgium
<sup>6</sup>Istitute of Plasma Physic and Laser Microfusion, Association EURATOM – IPPLM, Poland
<sup>7</sup>FOM Institute for Plasma Physics Rijnhuizen, Association EURATOM-FOM, PO Box 1207, 3430 BE Nieuwegein, The Netherlands
<sup>8</sup>LPP-ERM/KMS, Association EURATOM-Belgium State, B-1000 Brussels, Belgium
\* See annex of M.L. Watkins et al, "Overview of JET Results ", (Proc. 2<sup>§†</sup> IAEA Fusion Energy Conference, Chengdu, China (2006)).

> Preprint of Paper to be submitted for publication in Proceedings of the 34th EPS Conference on Plasma Physics, (Warsaw, Poland 2nd - 6th July 2007)

#### **1. INTRODUCTION**

Understanding the origin of rotation in ICRF heated plasmas is important for predictions for burning plasmas sustained by alpha particles, as both are characterised by a large population of fast ions and no external momentum input. Recent experiments performed at JET investigated rotation in Ohmic and purely ICRF heated plasmas. The aim of recent experiments with ICRF heating was to establish under which conditions co and counter rotation arise and to build up a database on how intrinsic rotation in JET scales with the plasma current and ICRF heating details. Determination of the rotation induced with ICRF heating requires taking into account the rotation in Ohmic heated plasmas. Previous studies of rotation with Ohmic heating were in limiter plasmas, here studies in the divertor configuration are reported.

#### 2. MEASUREMENT TOOLS

Plasma rotation was determined from charge exchange recombination spectroscopy, X-ray crystal spectroscopy and the observed frequency of MHD modes. (a) Toroidal angular frequency profiles were obtained from Charge Exchange Recombination Spectroscopy (CXRS) of C<sup>+6</sup> [1] during short NBI pulses (typical duration of 200ms and  $P_{NBI} \sim 1MW$ ). In the normal JET configuration, i.e.  $B_T // I_p$  and no toroidal field ripple, NBI provides a toroidal momentum source in the direction of the plasma current (cocurrent rotation). Thus, for diagnostic purposes with ohmic and ICRF heating, only measurements taken within the first 50ms have been used. (b) The toroidal angular frequency in the plasma core has also been measured with a high resolution X-ray Crystal Spectrometer (XCS) that observes the spectrum near the resonance line of the helium-like nickel (Ni<sup>+26</sup>) [2]. In JET divertor configuration, where the level of impurity is reduced and, for the low frequencies studied here, both CXRS and XCS measurements are at the limit of detection. Special consideration was taken in improving measurement statistics. (c) Further information on plasma rotation at different radial positions was obtained from MHD modes' frequency and mode number analysis.

#### 3. OHMIC HEATED PLASMAS

Early studies with X-ray crystal spectroscopy indicated that the core of JET Ohmic limiter plasmas rotated counter to the toroidal plasma current [3]. In the present study XCS was used to analyse preheating phases in the divertor configuration (fig.1). The method of spectral and Doppler shift analysis is described in detail in [4]. In the early rotation frequency measurements, the wavelength scale was calibrated by comparison with the observed sawtooth precursor frequencies [1]. In the present analysis, a reference wavelength for the Doppler shift of the Ni<sup>+26</sup> line was obtained by comparison with the derived CXRS measurements of C<sup>+6</sup> at different NBI power levels (fig.2). During the Ohmic divertor phase Ni levels are too low. In order to improve measurement statistics, spectra analysed with an integration time of 30ms have been added over extended phases lasting up to 2s under steady state conditions. Figure 1 shows that the core of Ohmic plasmas in the divertor configuration are counter rotating. In the convention used here, positive frequency means cocurrent and negative means counter-current rotation. The observation of core counter rotation is consistent with angular frequency profile

measurements with charge exchange recombination spectroscopy that show hollow counter rotating profiles (as illustrated in fig.4). In contrast, the outer half of the plasma is co-rotating.

#### 4. ICRF HEATED PLASMAS

ICRF heated plasmas have been previously observed to either co or counter rotate [5, 6]. Recent JET experiments studied rotation in L-mode plasmas with  $B_T = 2-2.75T$ ,  $I_p = 1.2-2.6MA$  and ICRF heating  $(P_{ICRF} = 3-6MW$ , resonance position 40cm off-axis on the high field side). The object was to establish under which conditions co- and counter-current rotation arises and to establish a database on how rotation in JET scales with various parameters such as the plasma current, position of the cyclotron resonance and the antenna phasing A typical discharge is shown in figure 3. Short NBI pulses were used intermittently for rotation profile measurements with charge exchange recombination spectroscopy. CXRS angular frequency profiles obtained at the beginning of the NBI blips indicate that the core rotation depends on the value of the plasma current (as illustrated in figure 4). At the lowest plasma currents,  $I_p \sim 1.2$ -1.7MA, hollow profiles with the core counter rotating, similar to observations in the Ohmic plasmas were observed. At the high plasma current, Ip~2.6MA, peaked co-rotating profiles, were observed, even though ICRH was applied off-axis. Figure 5 shows the central angular frequency as a function of Ip from a database of 21 discharges. At the higher plasma currents where sawtooth precursors were clearly identified, MHD mode frequencies indicated significant plasma acceleration in the co-current direction as the ICRF power is stepped up (fig. 6). The increase in the observed MHD mode frequency could neither be attributed to an increase in  $\omega_i^*$ , as T<sub>i</sub> remained constant, nor to a radial shift in the mode location. In order to study the possible influence of MHD instabilities on rotation profiles, discharges with and without sawtooth crashes (with  $q_0>1$ ) were produced. These were either obtained by early X-point formation and RF heating applied before the plasma current was fully penetrated or in a few cases by application of 2MW of Lower Hybrid Current Drive (LHCD) [7]. The range of central rotation frequency values (-6krad/s to +10krad/s) was the same in discharges with or without sawtooth. In addition, no correlation was found between profile shape and sawtooth period. The edge as in the Ohmic cases was co-rotating in all cases, with the edge frequency scaling with  $W_{DIA}/\bar{n}_e$ , where  $W_{DIA}$  is the plasma stored energy and  $\bar{n}_e$  is the line integrated density [7].

#### SUMMARY

The central region of Ohmic plasmas in the JET divertor configuration are counter rotating with toroidal frequencies up to -8 krad/s. ICRF heated plasmas have been found to either co or counterrotate with central angular frequencies ranging from -6krad/s to +10krad/s. Once the Ohmic rotation is subtracted, one finds in most cases co-current acceleration when ICRF power is applied. In addition, the ICRF induced rotation appears to originate in the plasma core and it was found to be sensitive to the plasma current. The differences in frequency profile shape cannot be attributed to differences in sawtooth instability. The outer part of the plasma is observed to rotate in the co-current direction independently of heating scenario.

#### ACKNOWLEDGEMENTS

This work was performed under the European Fusion Development Agreement. It received financial support from Fundação para a Ciencia e Tecnology (FCT), Portugal, from the United Kingdom Engineering and Physical Sciences Research Council and from EURATOM. The view and opinions expresses herein do not necessarily reflect those of the Europeann Commission.

### REFERENCES

- [1]. C.R. Negus et al., Rev. Sci. Instrum. 77 (2006) 10F102
- [2]. F. Bombarda et al, Phys. Rev. A 37 (1988) 504
- [3]. R. Giannella et al, Journal de Physique; Supplément au no 3, 49 (1988) C1-283.
- [4]. L-G Eriksson, E Righi and K-D Zastrow, Plasma Phys. Control. Fusion 39,27 (1997)
- [5]. J-M. Noterdaeme et al. NF 43, 274 (2003)
- [6]. L-G. Eriksson et al, PRL 992, 235001 (2004)
- [7]. L-G. Eriksson et al, 17th Topical Conf on Radio Frequency Power in Plasmas, Clearwater, Florida, USA (2007).



Figure 1: Typical discharge used for XCS calibration ( $B_T = 2T$ ,  $I_p = 2.5MA$ ,  $P_{NBI} = 2.5-11.3MW$ ) with a flat top Ohmic phase, after X-point formation (indicated by vertical dotted line) with 2-3s duration.(a) NBI Power; (b)  $B_T$  and  $I_p$ , (c) Intensity of Ni<sup>26+</sup> obtained with an integration time of 30ms; (d) Core angular frequency time determined from XCS.



Figure.2 - Comparison of measurements of toroidal angular frequency of  $C^{+6}$  and  $Ni^{+26}$  at the same radius  $(Ni^{+26} < R > = 3.2 - 3.8m.)$ .



Figure 3: Typical discharge with ICRF off-axis heating and dipole phasing ( $B_T = 2.6T$ ,  $I_p = 2.6T$ ). The rotation profiles obtained during the first NBI blip, t=19s, are shown in figure 4.



Figure 4: CXRS Toroidal Angular Frequency Profiles for similar discharges: (a)  $I_p = 2.6MA$  with ICRH (see fig. 3), (b)  $I_p = 1.7MA$  with identical ICRH (c) reference Ohmic plasma with NBI blips but no ICRH. The 1st reliable profile is shown in red and a profile at the end of the blip is shown in blue. The times are from the start of the blip.



Figure 5: Central Toroidal Angular Frequency from CXRS measurements versus  $I_{p}$ .



Figure 6: Spectrogram of magnetic pick up signal showing frequency of sawtooth precursors that increase with  $P_{ICRF}$ .