

EUROFUSION CP(15)04/14

C. Pardanaud et al.

Raman Microscopy Investigation of Beryllium Materials

(18th May 2015 – 22nd May 2015) Aix-en-Provence, France



This work has been carried out within the framework of the EUROfusion Consortium and has received funding from the Eurotom research and training programme 2014-2018 under grant agreement No 633053. The views and opinions expressed herein do not necessarily reflect those of the European Commission. "This document is intended for publication in the open literature. It is made available on the clear understanding that it may not be further circulated and extracts or references may not be published prior to publication of the original when applicable, or without the consent of the Publications Officer, EUROfusion Programme Management Unit, Culham Science Centre, Abingdon, Oxon, OX14 3DB, UK or e-mail Publications.Officer@euro-fusion.org".

"Enquiries about Copyright and reproduction should be addressed to the Publications Officer, EUROfusion Programme Management Unit, Culham Science Centre, Abingdon, Oxon, OX14 3DB, UK or e-mail Publications.Officer@euro-fusion.org".

The contents of this preprint and all other EUROfusion Preprints, Reports and Conference Papers are available to view online free at http://www.euro-fusionscipub.org. This site has full search facilities and e-mail alert options. In the JET specific papers the diagrams contained within the PDFs on this site are hyperlinked.

Raman microscopy investigation of beryllium materials.

C Pardanaud^{1,*}, M I Rusu^{1,2}, G Giacometti¹, C Martin¹, Y Addab¹, P Roubin¹, C P Lungu³, C Porosnicu³, I Jepu³, P Dinca³, M Lungu³, O G Pompilian³, R Mateus⁴, E Alves⁴, M Rubel⁵ and JET contributors^{6**}

¹ Aix Marseille Université, CNRS, PIIM UMR 7345, 13397, Marseille, France * cedric.pardanaud@univ-amu.fr

²National Institute of R&D for Optoelectronics INOE 2000, 409 Atomistilor Street, P.O. Box MG-5, 077125, Magurele, Ilfov, Romania

³ National Institute for Laser, Plasma and Radiation Physics, 077125, Magurele-Bucharest, Romania ⁴ Instituto de Plasmas e Fusão Nuclear, Instituto Superior Técnico, Universidade de Lisboa,

Av. Rovisco Pais, 1049-001, Lisboa, Portugal

⁵ Department of Fusion Plasma Physics, Royal Institute of Technology (KTH), 100 44 Stockholm, Sweden ⁶EUROfusion Consortium, JET, Culham Science Centre, Abingdon, OX14 3DB, UK

We report for the first time on the ability of Raman microscopy to give information on the structure and composition of Be related samples mimicking plasma facing materials that will be found in ITER. For that purpose, we investigate two types of material. First: Be, W, Be₁W₉, and Be₅W₅ deposits containing a few percents of D or N, and second: a Mo mirror exposed to plasma in the main JET chamber (in the framework of the first mirror test in JET with ITER-like wall). We performed atomic quantifications using ion beam analysis for the first samples. We also did atomic force microscopy. We found defect induced Raman bands in Be, Be₁W₉, and Be₅W₅ deposits. Molybdenum oxide has been identified showing an enhancement due to a resonance effect in the UV domain.

^{**} See the Appendix of F. Romanelli et al., Proceedings of the 25th IAEA Fusion Energy Conference 2014, Saint Petersburg, Russia

1. Introduction

In a tokamak, understanding and being able to predict the evolution of the plasma facing components (PFC) that interact with the plasma is one of the keystones to make nuclear fusion a way of producing energy in the future [1]. The inner walls of the future international reactor ITER that will receive most of the particle flux and/or heat loads will be composed of tungsten and beryllium [2]. Mirrors used for optical spectroscopy and imaging systems for plasma diagnostics, less exposed but still interacting with the plasma and impurities, will be made of metals, and first tests have been done recently in JET with the ITER-like wall (JET-ILW) configuration [3] using molybdenum and coating of rhodium. In that framework, the surface morphology and composition changes under operation that will lead to changes in the material properties have to be measured and understood. The migration and/or melting of elements in the machine [4-6], the production of dust [7], the hydrogen isotope retention with a safety issue [8], the impurity contamination (oxidation,...) [9] and the complex surface erosion [10-11] have to be taken into account when trying to predict degradation or lifetime of these PFC. Surface characterisation tools are then necessary to help interpretation.

Among surface characterisation tools, Raman microscopy is a nondestructive, non contact, and local $(\approx 1 \mu m^2 \text{ lateral resolution})$ technique, and is of interest for the analysis of samples in relation with plasma wall interactions occurring in tokamaks [12]. It is based on the inelastic scattering of visible or UV photons with a lattice quantum vibration (phonon). As the incident photon looses energy corresponding to the quantum vibration of a given chemical bond, this technique gives an information on the chemical composition of the surface probed. It is sensitive to the surrounding of these chemical bonds, it can give information on the structure at the nanometric scale and on defects,...

In this paper we study the ability of Raman microscopy to give information on the structure and composition of Be related samples, using first: Be, W, Be_xW_y deposits, without or with D or N and second the JET-92 polycristalline Mo mirror exposed in JET-ILW during the First Mirror Test in JET [3]. The paper is organized as follows: experimental details are given in Section 2, results corresponding to the two kind of samples are given in section 3.1, and 3.2, respectively. Conclusions are given in Section 4.

2. Experimental details

Depositions of 400 nm thick Be, W and Be_xW_y (x=1,y=9 and x=5, y=5 at.%) layers were performed on silicon substrates using the thermionic vacuum (TVA) method for which the emission of an electron beam produced by a heated filament is focused using a special Wehnelt device toward an anode connected to a high voltage regulated power supply. More details can be found in [13] and references there in. The TVA plasma spatial localization allows gas injection close to the substrate during the deposition. Partial pressure of the Be/W in the substrate vicinity was in the range 10⁻³ 10⁻ ² Pa. N₂ or D₂ (partial pressures are two orders of magnitudes higher than the ones for the interest materials) were also introduced to trap N or D. Rutherford backscattering measurements (RBS) were carried out with 1.0, 1.4 and 2.0 MeV H⁺ and 2.2 MeV He⁺ beams for elemental depth profiling and film thickness evaluation. A beam of 2.3 MeV ³He⁺ were used for D quantification by nuclear reaction analysis (NRA).

We also studied the JET-92 Mo mirror introduced in the JET tokamak in the framework of the First Mirror Test in JET. This mirror was situated 1.5 cm deeper in the first channel of the cassette than the JET-93 sample studied in [3]. The surface concentrations of Be, C and O (given in 10^{15} atom cm⁻²) are 3.3-12.5, 34-76, 37, respectively.

Raman spectra were recorded using a Horiba-Jobin-Yvon HR LabRAM apparatus in the backscattering geometry (with x100 objective, with a numerical aperture of 0.9 for. $\lambda_L = 514.5$ and 632.8 nm, and x40 for $\lambda_L=325$ nm). The laser power was kept at ~ 1mW μ m⁻². The Raman mapping mode was also used, and sometimes necessary to increase the signal to noise ratio. Note that to conserve momentum during the scattering, UV-visible photons can only probe the optical phonons in the center of the brillouin zone corresponding to the probed crystal (called sometimes the q=0 selection rule). The AFM (an AFM-NTMDT solver) was used in the tapping mode.

3. Results and discussions

3.1. Be, W and $Be_x W_y$ deposits



Figure 1. Normalized Raman spectra of Be, $Be+D_2$ and $Be+N_2$ samples. The dotted spectrum is Be polycrystalline sample. The star is one of the BeO bands according to [13]. $\lambda_L=633$ nm.

Figure 1 displays the Raman spectra (λ_L =633 nm) of Be deposited by the TVA method, in presence of N₂, D₂ or without injected gas. The three spectra are compared to that of a commercial poly crystalline sample. The Be deposited sample is similar to that recorded on the reference crystalline sample taken as a reference, with a small full width at half maximum (8 cm⁻¹): this means that the Be deposited sample is crystalline. The position of the Be stretching band is 459 cm⁻¹. Compared to this spectrum, the sample deposited with D₂ shows a 3 cm⁻¹ downshift, a FWHM increase (11.5 cm⁻¹) and three new bands appear at 413, 548 and 634 cm⁻¹, the last one being close to the 645 cm⁻¹ band attributed to beryllium oxide [14] (marked by a star in figure 1). The sample deposited with N₂ shows a 6 cm⁻¹ decrease of the Be stretching band, a FWHM increase (17 cm⁻¹). They are defect induced bands due either indirectly to Be-D of Be-N bonds or directly to defects caused during the bombardment.

These observations can be related to AFM observations (not shown here) showing the existence of a nanometric roughness which could induce phonon confinement explaining the defect induced band intensity.



Figure 2. Raman spectra of the pristine Be, W, Be_1W_9 and Be_5W_5 samples deposited by TVA method. Color legends are the same as in figure 1. $\lambda_L = 514$ nm.

Figure 2 displays the Raman spectra of Be, W, Be_1W_9 and Be_5W_5 deposited without or with D_2 or N_2 . For the Be sample (top spectra), the bands in the 700 - 1100 cm⁻¹ region are attributed to beryllium oxide. For W deposited (bottom spectra) without or with D₂ or N₂, the Raman spectra should be flat, according to the q=0 selection rule. The weak bands observed at 350 cm⁻¹ and in the 700-1000 cm⁻¹ region that we attribute to surface tungsten oxide are due to air contamination when storing the sample at ambient conditions. For Be_1W_9 (middle spectra) without and with D_2 or N_2 , as for Be₅W₅, no more Be stretching band is observed at 459 cm⁻¹, meaning Be is bonded with W to form an alloy. Surface tungsten oxide is visible, with a diminution noticed for the Be_5W_5 samples, due to a lower amount of W under the laser beam compared to Be1W9 or W samples. Two new bands appear at 139 and 206 cm⁻¹. Their shape is roughly the same whatever the sample, meaning it is not attributed to a bond involving deuterium nor nitrogen. The Be/W atomic ratio are 0.097, 0.125 and 0.110 for Be₁W₉ without and with D₂ or N₂, respectively. It is 1.45, 0.90 and 1.02 for Be₅W₅ without or with D₂ or N₂, respectively. The intensity of these 139 and 206 cm⁻¹ bands is hard to interpret as we noticed it can vary from one location of a sample to another location. Note that the amount of N (3 to 8 at. %) or D (<0.4 at.%) does not influence so much the spectra for W and Be_xW_y samples. The 139 and 206 cm⁻¹ bands are then not related to the amount of D or N but may be attributed to a selection rule relaxation due to a folding of the W acoustic phonon dispersion putting at the center of the Brillouin zone all the vibrations because of Be impurities. This is also supported by the fact that the phonon density of state of W is double and look like our bands [15].

The oxygen content is 9 and 3.3 at. % in $Be+D_2$ and $Be+N_2$ samples, respectively. For the Be film the results didn't give a conclusive evidence for the presence of oxygen above the detection limit, 0.1 at% in the spot analyzed. The result do not contradict the Raman since the presence of a inhomogeneous distribution of BeO diluted in the film would be difficult to determined by RBS. The oxygen content in the W, W+D₂ and W+N₂ could not be measured by RBS analyses.

3.2. Be containing deposit in Mo JET mirror



Figure 3. JET-92 mean Raman spectra corresponding to two zones on the sample. The upper spectrum is representative of the majority of the sample. The lower one is representative of $a \approx 0.5 \times 0.5 \text{ mm}^2$ region (right inset). $\lambda_L = 325 \text{ nm}$.

Raman spectra with λ_L =514 nm were first obtained on the JET-92 sample, with a very poor signal to noise ratio, not exploitable. Using λ_L =325 nm improved drastically the situation, meaning the laser used is in resonance with an electronic level of the solid [16]. Figure 3 displays two Raman spectra obtained by summing spectra recorded on two ≈25x25 µm² zones (i.e. Raman mappings mode), using λ_L =325 nm. The zones of interest are at the center of the sample (representative of the majority of the sample surface), and at one corner. On most of the surface, optical microscopy show the existence of homogeneously distributed micrometric dots, but on the corner zone, some micrometric radial patterns have been observed by electron and atomic force microscopies (see figure 3 inset for electron microscopy), with ≈ 10 nm height (AFM measurements not shown here). The origin of such patterns is unknown. Everywhere except on such patterns, spectra are mainly due to molybdenum oxide, as in [17]. Bands at \approx 500, 700, and 830 cm⁻¹ are attributed to bulk Mo-O bonds, and one band at 950 cm⁻¹ is attributed to surface Mo=O bonds. On the pattern, the signature is several times higher (\approx 25 x times) than everywhere on the sample, and the spectrum is changed, being composed mainly of two very thin and intense bands at 919 and 951 cm⁻¹. A band observed at 1830 cm⁻¹ may be due to a combination of the two last bands, exhibiting anharmonic effects [18]. Bands attributed to C-O and C=O bands are observed at 1250 and 1640 cm⁻¹. In the 400-700 cm⁻¹, several bands are observed close to the position of the defect induced bands in beryllium, shown in figure 1, but with no clear origin. The doublet at 919/951 cm⁻¹ is related to Mo=O bonds. One possible interpretation is that the two frequencies are attributed to two surface Mo=O environments. As the top layer (few nm) contains C and Be, it could reasonably be interpreted as due to Be or C bonded on the surface oxygen atoms.

The origin of this oxide formation is not yet clear but may partially be due to air storage of the Mo mirrors before they were transferred in JET, as mentioned in [3]. The same analysis realized on Mo mirrors stored in air for some years and not exposed in JET should be done to answer the question of the role of oxygen impurities on JET mirrors.

4. Conclusion

We demonstrate the ability of Raman microscopy to give information on the way elements are bonded on PFC containing Be. The presence of defect bands in the deposited Be (400-640 cm⁻¹ spectral window) and deposited Be_xW_y (139 and 206 cm⁻¹ bands) were observed in the samples. We also report on the detection of Molybdenum oxide formed on the Mo mirror after submitted to plasma wall interactions in JET-ILW. We also report on the existence of a UV Raman resonance effect that increases significantly the Raman signal, allowing to show bulk Mo-O bonds, surface Mo=O bands, and possibly bond creation between surface oxygen and Be or C. This UV resonance coincides with the reflectivity degradation reported in the 250 - 400 nm range. Mo=O bonds are exalted 25 times on some nanometric roughness found on a $0.5 \times 0.5 \text{ mm}^2$ zone. The results put in evidence the potential of Raman microscopy to study qualitatively PFM evolution due to operations but a more systematic comparison with controlled laboratory samples made in controlled conditions is necessary.

Acknowledgements

This work has been carried out within the framework of the EUROfusion Consortium and has received funding from the Euratom research and training programme 2014-2018 under grant agreement No 633053. The views and opinions expressed herein do not necessarily reflect those of the European Commission. C Pardanaud and MI Rusu acknowledge the *Fondation Aix-Marseille Université* for funding the postdoctoral postion.

References

[1] Neu R et al 2011 Plasma Physics and Controlled Fusion 53 124040

[2] Philipps V 2011 Journal of Nuclear Materials 415 S2-S9

[3] Ivanova D et al 2014 Physica Scripta T159 014011

[4] Coenen J W et al 2013 Nuclear Fusion 53 073043

[5] Krieger K et al 2013 Journal of Nuclear Materials 438 S262-S266

[6] Schmid K Reinelt M and Krieger K 2011 Journal of Nuclear Materials, 415 S284-S288

[7] Rosanvallon S Grisolia C Delaporte P Worms J Onofri F Hong S H Counsell G and Winter J 2009 *Journal of Nuclear Materials* **386–388** 882-883

[8] Loarer T et al, 2007 Nuclear Fusion, 47 1112-1120.

[9] Tsitrone E 2007 Journal of Nuclear Materials 363–36512-23

[10] Mellet N et al 2014 Nuclear Fusion 54 123006

[11] Brezinsek S et al 2014 Nuclear Fusion, 54 103001

[12] Pardanaud C Addab Y Martin C Roubin P Pegourié B Oberkofler M Köppen M Dittmar T

Linsmeier Ch 2015 Physica Status Solidi (c) 12 98-101

[13] Lungu C P et al 2014 Vacuum 110 207-212

[14] Jahn M Mueller M Endlich M Neel N Kroeger J Chis V Hellsing B 2012 *Physical Review B* 86 085453

[15] Crocombette J-P Notargiacomo P Marinica M-C 2015 Journal of Physics: Condensed Matter 27 165501

[16] Li C 2003 Journal of Catalysis 216 203-212

[17] Rouhani M Hobley J Subramanian G S Phang I Y Foo Y L Gorelik S 2014 *Solar Energy Materials and Solar Cells* **126** 26-35

[18] Kim H Kosuda K M Van Duyne R P and Stair P C 2010 Chemical Society Reviews 39 4820-4844