



EUROfusion

WPTFV-CPR(18) 18810

S Varoutis et al.

Assessment of the 3D geometrical effects on the DEMO divertor pumping efficiency

Preprint of Paper to be submitted for publication in Proceeding of 23rd International Conference on Plasma Surface Interactions in Controlled Fusion Devices (PSI-23)



This work has been carried out within the framework of the EUROfusion Consortium and has received funding from the Euratom research and training programme 2014-2018 under grant agreement No 633053. The views and opinions expressed herein do not necessarily reflect those of the European Commission.

This document is intended for publication in the open literature. It is made available on the clear understanding that it may not be further circulated and extracts or references may not be published prior to publication of the original when applicable, or without the consent of the Publications Officer, EUROfusion Programme Management Unit, Culham Science Centre, Abingdon, Oxon, OX14 3DB, UK or e-mail Publications.Officer@euro-fusion.org

Enquiries about Copyright and reproduction should be addressed to the Publications Officer, EUROfusion Programme Management Unit, Culham Science Centre, Abingdon, Oxon, OX14 3DB, UK or e-mail Publications.Officer@euro-fusion.org

The contents of this preprint and all other EUROfusion Preprints, Reports and Conference Papers are available to view online free at <http://www.euro-fusionscipub.org>. This site has full search facilities and e-mail alert options. In the JET specific papers the diagrams contained within the PDFs on this site are hyperlinked

Assessment of the 3D geometrical effects on the DEMO divertor pumping efficiency

S. Varoutis, Yu. Iglikhanov, Chr. Day,
Karlsruhe Institute of Technology (KIT),
Institute of Technical Physics, Vacuum Department
Karlsruhe, Germany
stylianos.varoutis@kit.edu

Abstract— In the present work, a parametric analysis by using the DIVGAS code is performed in order to highlight the influence of the inter-cassette gaps and the existence of the dome on the overall pumping efficiency of the DEMO divertor. For this fundamental study, a 3D divertor configuration is chosen, in which deuterium neutral particles are assumed to penetrate the private flux region. The chosen incoming boundary conditions correspond to high-collisionality divertor operational conditions. It has been found that in the case for a divertor without a dome the particle losses through the separatrix are dominating and consequently the effect of 3D leakages on the pumping efficiency is small. For the gap reference case of 20 mm width with the dome and low capture coefficients, the pumping efficiency is 9 times higher than for the case without the dome. In general, if there is a dome, it eliminates the outflux of neutrals towards the x-point and forces the neutrals to move downwards in the sub-divertor vicinity, finally achieving a neutral compression. In consequence of which the pumping efficiency increases and the gaps show a relatively higher impact.

Keywords—*DEMO reactor; divertor; fueling; pumping efficiency; DSMC method; neutral modelling.*

I. INTRODUCTION

The DEMO divertor system comprises 54 individual cassettes. The cassettes are not perfectly sealed but have, for reasons of mechanical tolerances, gaps between each other. As a consequence, unintended particle fluxes will occur both in poloidal and toroidal directions and between the divertor cassettes. This issue has been already investigated for the case of Alcator C-Mod [1], in which the influence of the gaps in the poloidal and toroidal direction is significant and only if their existence is assumed, the corresponding numerical and experimental results may coincide. Furthermore, the same study has been performed for the case of ITER [2], where the simulations indicate that the parasitic flows caused by these gaps can be comparable to the pumping throughput. Similar conclusions were drawn in [3] where it has been found that a very strong back streaming of gas into the plasma occurs, mainly due to the flows through the inter-cassettes gaps. Furthermore, a recent study has been performed for the case of a 3D DEMO divertor [4] without a dome in which the assumed divertor plasma conditions correspond to low divertor pressure levels (i.e low divertor collisionality). This work has for the first time introduced the aspect of the pumping efficiency, defined as the ratio of the pumped over the net incoming neutral particle flux, considering the inter-cassettes gaps. There, the analysis has shown that for small gaps the pumping efficiency is almost independent of the gap width, while for large values of the gap width the pumping efficiency may be reduced by 20%. Furthermore, as there is no dome, almost 80% of the incoming to private flux region (PFR) neutral particles were found to move towards the x-point, independent of the gap width.

The present work is a continuation of the study presented in [4], in which the main divertor 3D geometry was kept the same but additionally the dome structure has been added as well as higher divertor pressure levels in PFR (i.e high divertor collisionality), more relevant to DEMO operational conditions, have been assumed. Regarding the presence of the dome, it is noted that its primary function is to achieve a high compression of neutrals in the PFR in order to increase the pumping efficiency. Additionally, the dome may reduce the neutral outflux towards the plasma core through the x-point and shield the pumping port against neutrons.

The present analysis will allow defining the design space and the impact of the dome and the inter-cassettes gaps on the overall pumping efficiency of the DEMO divertor, which is still under an ongoing conceptual design phase. The ultimate goal is to define an optimum divertor design in terms of its pumping efficiency, using as the main driver the particle transport physics.

II. DIVERTOR GEOMETRY

The current model of a 20° degree DEMO divertor segment is shown in Fig.1. The presented divertor configuration is based on the 2015 EU DEMO baseline design [5], which includes in total 54 divertor cassettes and has a major radius equal to $R=9.1$ m. Five different geometrical configurations have been studied in which the width d of the poloidal and toroidal gaps varies between 0 to 40 mm. The inter-cassette gap width equal to 20 mm is assumed here as a reference case. In Fig. 2a, the 3D DEMO divertor configuration, which corresponds to a 20° degree sector and includes the dome and the toroidal and poloidal gaps, is shown. For representation purposes, the plane KK' is additionally introduced.

In Fig. 2b, a 2D cut along the KK' plane of the applied 3D model is depicted. In this specific design, the particles, which enter the pumping port and reach its outlet, have the possibility to flow in the toroidal or poloidal direction (not shown here) in the volume between the divertor cassette and the vacuum vessel. The adsorbing surface D named as pumping slot in this case is located further below the pumping port outlet and a given capture coefficient ξ (i.e the probability of a particle to be pumped from there) is appointed. Consequently, ξ takes values between $0 \leq \xi \leq 1$. In the present work, the capture coefficient has been varied, namely $\xi=0.1, 0.3, 0.6$ and 1.0 . If the particle is not finally exhausted at the pumping slot, then it undergoes a diffuse reflection, assuming that the temperature at the entrance to the pumping port is equal to 420 K. The total area of the pumping slot is equal to 2.1 m². The surfaces A and B in the HFS and LFS correspond to the virtual windows, through which neutrals penetrate the PFR and on which the incoming boundary conditions are imposed. The corresponding area for each surface is 1.6 m² and 2.8 m² respectively. The surfaces E and F represent the boundaries through which the neutrals will enter the scrape-off layer (SOL) and it is assumed that they will be immediately ionized and removed from the computational domain. Finally, the height of the dome is constrained by the predefined x-point and in this work the distance of the bottom dome surface from the pumping slot is equal to 1.46 m.




Fig.1. Three dimensional DEMO 2015 divertor configuration including three divertor cassettes, the dome, the first wall and the surrounding vacuum vessel.




Fig.2. a) A 20° degree DEMO divertor sector including the dome structure, the plane KK' as well as the symmetry planes, b) A 2D cut along the KK' plane.

III. NUMERICAL METHOD AND BOUNDARY CONDITIONS

The DIVGAS code, which is based on the Direct Simulation Monte Carlo (DSMC) method [6], has been applied for the numerical modelling of the configuration under consideration. A detailed description of this method is omitted and the reader may consult the following publications [7-10] for further details. Here, only crucial simulation parameters are mentioned. In brief, in all the present simulations an optimum value of time step $\Delta t = 0.01$ μ s has been applied. On the other hand, the average number of particles in each simulation ranges between 10^7 to 2×10^7 . This number assures that the statistical scattering of macroscopic quantities along the computational domain is sufficiently low. An unstructured tetrahedral grid is applied, with the number of cells to be equal to 2×10^6 . The applied grid was chosen such that the cell size is much smaller than the local mean free path. Due to the high collisionality flow regime met in the divertor area, the computational effort is quite challenging. This work was performed on the MARCONI HPC with 200 CPUs for each run, and the typical time for reaching steady state conditions was several weeks. For all simulated cases the particle balance of the total incoming and outgoing particles in the flow domain is fully satisfied.

The imposed boundary conditions assume that pure molecular deuterium (D_2) gas enters the sub-divertor area through the virtual windows A and B (see Fig. 2b) with reference pressure P_0 and temperature T_0 equal to 1 and 10 Pa and 4023 K (or 0.35 eV) respectively. The high pressure case consists of a generic assumption based on former ITER relevant detached plasma scenario as described in [11]. However, currently ongoing DEMO simulations with SOLPS plasma code show that these boundary conditions can be considered as a representative case for the DEMO as well. The aforementioned macroscopic quantities P_0 and T_0 define the incoming neutral flux Φ^+ , as shown in Fig. 2b, while all the other particle fluxes would be estimated as an outcome of each simulation. The particle flux Φ^+ is yielded by assuming Maxwellian distribution of incoming neutrals using the expression

$$\Phi^+ = \frac{1}{4} S \frac{P_0}{k_B T_0} v_{th}, \quad (1)$$

where S is the area of the virtual windows A and B, k_B the Boltzmann constant and v_{th} is the mean thermal velocity. In addition, the net particle flux $\Phi_{in,net}$ is introduced and is equal to $\Phi_{in,net} = \Phi^+ - \Phi^-$. It is noted that, in the following section, all the presented particle fluxes are normalized based on the $\Phi_{in,net}$ quantity. Moreover, in the present work the ionization, dissociation and recombination processes on the walls and in the gas phase have not been taken into account. Therefore, when a deuterium molecule hits a stationary wall or the bottom part of the dome, it remains as molecule and a purely diffuse reflection takes place, where the incident molecule is reemitted with Maxwellian distribution based on the wall temperature, equal to $T_{wall}=420K$.

V. RESULTS AND DISCUSSION

A. Particle flux through the inter-cassette gaps

In Fig. 3 the normalized particle flux through all the toroidal and poloidal gaps in terms of the gap width is presented, for the cases with and without dome as well as different imposed incoming to PFR boundary conditions and capture coefficients. It is seen that in general the normalized particle flux increases with the gap width, while inverse behavior is observed in the case of the capture coefficient ξ , namely the particle flux through the gaps decreases with increasing capture coefficient. Moreover, the impact of the dome can be seen in Fig. 3. In the case without the dome, the normalized particle fluxes are significantly smaller, and the pressure P_0 of incoming to PFR neutrals, has only a weak impact on the particle flux through the gaps compared with the corresponding case with the dome. The existence of the dome facilitates higher particle fluxes through the gaps and as representative example the reference case of 20 mm gap width is chosen for demonstration purposes. For a capture coefficient equal to $\xi=0.1$ and $P_0=10$ Pa, the normalized flux through the gaps is increased by a factor of ~ 7 in the case with dome, compared with the corresponding case without one.




Fig.3. Normalized particle flux through the toroidal and poloidal gaps in terms of the gap width. The cases with and without dome as well as different incoming boundary conditions and capture coefficients are considered.

B. Outflux of neutrals towards the x-point

As it was observed in our recent work [4], in the case without the dome a strong outflux of neutrals moving towards the x-point is observed. The outflux represents almost 80 to 90% of the incoming neutral particles and is almost independent from the gap width. In Fig. 4, the results of the normalized outflux in terms of the gap width are presented for different capture coefficients ξ and different imposed incoming to PFR boundary conditions. For comparison purposes the results presented in [4] are additionally considered. It is seen that indeed the outflux is weakly dependent on gap width for any capture coefficient ξ and P_0, T_0 . On the other hand, when the imposed neutral pressure P_0 increases by an order of magnitude, then the outflux is reduced by about 5%. In

general, it is noted that the outflux in the case without dome dominates the gap losses and therefore the effect of the gaps is less pronounced compared with the case with dome.




Fig.4. Normalized outflux in terms of the gap width. The case without dome as well as different incoming boundary conditions and capture coefficients are considered.

C. Pumped particle flux

In Fig. 5 the normalized pumped flux in terms of the gap width is presented, for the cases with and without dome as well as different imposed incoming to PFR boundary conditions and capture coefficients ξ . It is observed that in the case without dome, the pumping efficiency is very low and almost independent from the gap width, since the outflux dominates the particle balance in the PFR. Moreover, in the case without the dome, a modest dependence of pumping efficiency on the incoming boundary conditions is observed. More specific, for capture coefficient $\xi=0.1$ and the reference case of 20 mm gap width, the pumped flux increases by a factor of ~ 1.37 , as the pressure of the incoming neutrals increases by one order of magnitude. On the other hand, for the case with the dome, the normalized pumped flux (i.e. the divertor pumping efficiency) decreases with increasing gap width. Furthermore, for the reference case of 20 mm and capture coefficient $\xi=0.1$, the pumping efficiency considerably increases by a factor of ~ 9 compared with the corresponding case without the dome.




Fig.5. Normalized pumped flux in terms of the gap width. The cases with and without dome as well as different incoming boundary conditions and capture coefficients are considered.

D. 2D vs 3D divertor representation

In order to assess the importance of the present 3D divertor simulations, a comparison is being performed between corresponding (i.e. means subject to the same incoming boundary conditions) 2D and 3D DEMO divertor representations. The

considered 2D flow domain corresponds to the 2D cut along the plane KK' (see Fig. 2a and 2b). The pressure and temperature of the incoming neutral particles were considered equal to $P_0=10$ Pa and $T_0=0.35$ eV respectively. In Table 1, the comparison between corresponding 2D and 3D simulations is being presented. For the reference case of 20 mm gap width and $\xi=0.1$, the relative difference between 2D and 3D representations is 10.6% and increases further as the gap width is increased. The same behavior is being observed for the case of the higher capture coefficient $\xi=0.3$. In general, it is deduced that as the gap width increases, the need to perform more detailed and time-consuming simulations, becomes of great importance.

Table 1: Normalized pumped flux $\Phi_{\text{pump}}/\Phi_{\text{in,net}}$ considering a 2D and 3D divertor representation.

	2D	3D	Δ (%)	2D	3D	Δ (%)
Gap width (mm)	$\xi=0.1$	$\xi=0.1$		$\xi=0.3$	$\xi=0.3$	
20	0.877	0.981	10.6	0.926	0.993	6.7
40	0.735	0.937	21.5	0.857	0.977	12.3

VI. CONCLUSIONS

In the present work a parametric analysis by using the DIVGAS code is performed in order to highlight the influence of the inter-cassette gaps and the existence of the dome on the pumping efficiency of the DEMO divertor. For this fundamental study, a 3D divertor configuration is chosen, in which D_2 neutral particles are assumed to penetrate the PFR. The chosen incoming boundary conditions correspond to a high-collisionality divertor case.

Based on the presented results, it can be concluded that in the case without the dome the particle losses through the separatrix are dominating and consequently the effect of 3D leakages on the pumping efficiency is small. To avoid these particle losses, for the reference case of 20 mm gap width and low capture coefficients, the addition of the dome increases the pumping efficiency 9 times compared to the case without the dome. The dome eliminates the outflux of neutrals towards the x-point and forces the neutrals to move downwards in the sub-divertor vicinity. Therefore, a neutral compression is being achieved, which facilitates the increase of the pumping efficiency.

With regard to DEMO, it has to be noted that the divertor design will have to reconcile also other requirements than those for particle exhaust as discussed in this paper. It is obvious that the gaps between the divertor cassettes cannot be completely eliminated due to manufacturability and accessibility in this area. The final design will hence be decided when the trade-offs between various options can be better evaluated.

ACKNOWLEDGMENT

This work has been carried out within the framework of the EUROfusion Consortium and has received funding from the Euratom research and training programme 2014-2018 under grant agreement No 633053. The views and opinions expressed herein do not necessarily reflect those of the European Commission. This work was performed within the 2nd cycle of MARCONI-FUSION HPC. The required computational resources were allocated under the project DIVGAS-KIT.

REFERENCES

- [1] D.P. Stotler, B. LaBombard, "Three-dimensional simulation of gas conductance measurement experiments on Alcator C-Mod", J. Nucl. Mater. vols. 337–399, pp. 510–514, 2005.
- [2] A.S. Kukushkin, H.D. Pacher, V. Kotov, D. Reiter, D. Coster and G.W. Pacher, "Effect of conditions for gas recirculation on divertor operation in ITER", Nucl. Fusion, vol. 47(7), pp. 698–705, 2007.
- [3] V. Hauer, Chr. Day, "ITER divertor gas flow modelling", FED, vols. 98-99, pp. 1775-1778, 2015.
- [4] S. Varoutis et al., "Effect of neutral leaks on pumping efficiency in 3D DEMO divertor configuration", FED, doi:[10.1016/j.fusengdes.2018.04.089](https://doi.org/10.1016/j.fusengdes.2018.04.089), 2018.
- [5] R. Wenninger et al., "The physics and technology basis entering European system code studies for DEMO", Nucl. Fus., vol. 57, pp. 016011, 2017
- [6] G. A. Bird, Molecular Gas Dynamics and the Direct Simulation of Gas Flows, Oxford University Press, Oxford, UK, 1994.
- [7] S. Varoutis et al., "Simulation of neutral gas flow in the JET sub-divertor", FED, vol. 121, pp. 13–21, 2017.
- [8] S. Varoutis et al., "Optimization of pumping efficiency and divertor operation in DEMO", Nucl. Materials and Energy, vol. 12, pp. 668-673, 2017.
- [9] F. Bonelli et al., "Self-consistent coupling of DSMC method and SOLPS code for modeling tokamak particle exhaust", Nucl. Fusion, vol. 57(6), pp. 066037, 2017.
- [10] Chr. Day, S. Varoutis and Yu. Igitkhanov, "Effect of the dome on the collisional neutral gas flow in the DEMO divertor", IEEE Trans. Plasma Sc., vol. 44(9), pp. 1636–1641, 2016.
- [11] A.S. Kukushkin, H.D. Pacher, V. Kotov, D. Reiter, D. Coster and G.W. Pacher, "Effects of the dome on divertor performance in ITER", J. Nucl. Mater., vols. 363-365, pp. 308-313, 2007.